

Declaration of performance: No. **CPR-NO1/0456**

1. Unique identification code of the product-type: **LATICRETE 4237 RAPID + CRETE 211 (powder + latex)**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
IMPROVED, TWO-COMPONENT, CEMENTITIOUS ADHESIVE FOR CERAMIC TILES
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Internal and external tiling on floors and walls**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Laticrete Nordic AS, Stanseveien 31, 0903 Oslo** www.laticrete.no
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **n/a**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **n/a**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance


Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	n/a	EN 12004:2007 + A1:2012
Bond strength as: - initial tensile adhesion strength	≥ 1,0 N/mm²	
Durability for: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm² ≥ 1,0 N/mm² ≥ 1,0 N/mm²	
Release of dangerous substances	See SDS	

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Morten Gaarud – Managing Director**
(name and function)

Oslo, 01/07/2013
(place and date of issue)


.....
(signature)

CE MARKING according to EN12004:2007+A1:2012

	 <p data-bbox="679 412 1050 506">Laticrete Nordic AS Stanseveien 31, 0903 Oslo www.laticrete.no</p>
<p data-bbox="347 546 1203 712">CPR-NO EN 12004:2007+A1:2012 LATICRETE 4237 RAPID + CRETE 211 (powder + latex) Improved, two-component, cementitious adhesive for internal and external tiling on floors and walls</p>	
Reaction to fire	n/a
Bond strength, as:	
Initial tensile adhesion strength	≥ 1,0 N/mm ²
Durability for:	
Tensile adhesion after heat ageing	≥ 1,0 N/mm ²
Tensile adhesion after water immersion	≥ 1,0 N/mm ²
Tensile adhesion after freeze/thaw cycles	≥ 1,0 N/mm ²
Release of dangerous substances	see SDS